

Declaration of Performance

LE/DoP-Nr. 046EN/CPR/2025-02-28

1. **Unique identification of the product type:** Mortise Locks
12300, 12302, 12310, 12312, 12340, 12400, 12410,
12430, 12500, 12501, 12511, 12402, 12412, 12100
2. **Intended use:** Emergency exit devices operated by a lever handle or push pad,
for use on escape routes
3. **Manufacturer:** Glutz AG
Segetzstrasse 13
CH-4502 Solothurn
Switzerland
4. **Authorised representative:** ./.
5. **Systems of assessment of constancy of performance:** System 1
6. **Harmonised standard:** EN 179:2008
- Notified body:** PfB Rosenheim NB-Nr. 1644 as issued the Certificate of con-
stancy of performance with the number
1644-CPR-057-24-003 to system 1 and essential characteristics
assessed from 7.1 to 7.6.

7. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
7.1 Ability to release (for doors on escape routes)	fulfilled (≤ 70N unloaded)	4.2.1 EN 179:2008
7.2 Durability of ability to release against aging and degradation (for doors on escape routes)	fulfilled (200.000 cycles)	4.2.1 EN 179:2008
7.3 Self-closing ability C (for fire/smoke doors on escape routes)	-	4.2.1 EN 179:2008
7.4 Durability of ability to release regarding Self- closing ability C against aging and degradation (for fire/smoke doors on escape routes)	-	4.2.1 EN 179:2008
7.5 Fire resistance E (integrity) and I (insulation) (for fire doors on escape routes)	-	4.2.1 EN 179:2008
7.6 Control of dangerous substances	-	4.1.29, EN 179:2008 Note 2 in ZA 1

8. The performance of the actual product is in conformity with the declared performance / perfor-
mances. The issue of the declaration of performance complying with regulation (EU) nr. 305/2011
is under the sole responsibility of the above-named manufacturer.

Solothurn, 28.02.2025



Marco Hauri
CEO



Stefan Häni
Head of Development Mechanic